

Masking Tape Hot Melt HM 7220

• DESCRIPTION

Economic high-grade masking tape with synthetic rubber adhesive. Product is suitable for all DIY applications, domestic and professional painting, simple and more complex jobs.

• PRODUCT APPLICATION

- DIY
- Window sealing
- General masking
- Domestic DIY and Industrial general painting
- Sealing
- Fixing
- Light duty packaging
- Window framing and sealing

• PRODUCT PROPERTIES

- Must be operated in room temperature
- Various surface options to cover special requirements
- Excellent tape to tape adhesion
- High initial tack
- Easy tear
- Excellent conformability
- Easy curving
- Easy application on uneven surfaces



Athens: 68, Varis Avenue, 166 73 Voula, Greece,
Tel.: +30 210 899 5388, Fax exports: + 30 210 899 5386
Factory: 3rd km Pr. rd Skala - Atalanti, 352 00 Atalanti,
Greece, Tel.: +30 223330 23725, Fax exports: + 30 22330
23756
info@atlas-tapes.gr, www.atlas-tapes.gr

EFFECTIVE: April 2014

TECHNICAL DATA SHEET

• NOMINAL VALUES

Backing	Impregnated Crepe Paper
Adhesive	Hot Melt (Solvent-free)
Tensile Strength TM 5004 by Afera	80 ± 15 (N/25mm)
Elongation at Break MD TM 5004 by Afera	8 ± 2 (%)
Adhesion to Steel TM 5001 by Afera	Over 6 (N/25mm)
Paper thickness	85 ± 15 (mic)
Application Range	General purpose
Paper Colors	White <input type="checkbox"/> Sharp Yellow <input checked="" type="checkbox"/>
Adhesive Color	White <input type="checkbox"/>

The following data are nominal values based on PSTC, Afera and other standard tests. Information herein is only for general guidance and does not guarantee for accuracy and completeness. The user must, by test or otherwise, determine suitability for this product. Our standard term and conditions of sale apply exclusively to all orders, and all liability for damages of any kind, is limited to the amount of product. We reserve the right to make changes without notice or obligation in our products and publications.

