

PVC 32mic high tack PV 801HT

• DESCRIPTION

SOLVENT BASED Natural rubber tape with additional cohesion properties. Carrier PVC 32mic film suitable for printing with ordinary flexographic printing machine, without the use of primer and release.

• PRODUCT APPLICATION

- Ease of print with standard flexographic machines without use of primer and release.
- Manual and automatic carton sealing
- Adhesion on uneven surfaces due to excellent adhesive power.
- Suitable for all sorts of packaging applications.
- Refrigeration use suitable. (Application at room temperature above 18°C)
- Temperature resistance after application.
- Suitable for use on most types of recyclable cartons, due to special adhesive compound.

• PRODUCT PROPERTIES

- Completely silent
- Hand tear able
- Excellent printability properties to satisfy the most demanding printing application
- Resistant to temperature changes
- Longevity of application
- Excellent adhesive power.



Athens: 68, Varis Avenue, 166 73 Voula, Greece,
Tel.: +30 210 899 5388, Fax exports: + 30 210 899 5386
Factory: 3rd km Pr. rd Skala - Atalanti, 352 00 Atalanti,
Greece, Tel.: +30 223330 23725,
Fax exports: + 30 22330 23756
info@atlas-tapes.gr, www.atlas-tapes.gr

EFFECTIVE: April 2014

TECHNICAL DATA SHEET

• NOMINAL VALUES

Backing	PVC
Adhesive	Solvent-based, Natural Rubber
Tensile Strength TM 5004 by Afera	160 ± 30 (N/mm ²)
Elongation at Break MD TM 5004 by Afera	75 ± 30 (%)
Adhesion to Steel TM 5001 by Afera	4 ± 1 (N/25mm)
Shear to Steel TM 5012 by Afera	Over 200 (h, 25mm x 25mm on stainless steel, 23°C)
Rolling Ball Task PSTC-6 (PSTC)	Under 3 (cm)
Film thickness	32 ± 10% (mic)
Film Colors	Transparent <input checked="" type="checkbox"/>
Adhesive Color	Transparent <input checked="" type="checkbox"/> Brown <input type="checkbox"/> White <input type="checkbox"/>

The following data are nominal values based on PSTC, Afera and other standard tests. Information herein is only for general guidance and does not guarantee for accuracy and completeness. The user must, by test or otherwise, determine suitability for this product. Our standard term and conditions of safe apply exclusively to all orders, and all liability for damages of any kind, is limited to the amount of product. We reserve the right to make changes without notice or obligation in our products and publications.

