



**ATLAS  
TAPES**

## Euromount DS DS 206.8

TECHNICAL DATA SHEET

### DESCRIPTION:

Black closed cell polyethylene foam, solvent based acrylic adhesive suitable for mounting applications.

### APPLICATIONS:

- Mounting applications.
- Fixing
- Automotive mounting.

ATHENS  
68 Varis Avenue  
16673 Voula, Greece  
Tel.: +30 210 8995388

ATALANTI  
3rd km Skala Atalanti Road  
35200 Atalanti, Greece  
Tel.: +30 22330 23725

[www.atlas-tapes.gr](http://www.atlas-tapes.gr)  
[info@atlas-tapes.gr](mailto:info@atlas-tapes.gr)

## ALL ABOUT TAPES



### NOMINAL VALUES:

#### Backing

Black closed-cell polyethylene foam

#### Adhesive

Clear self cross linked solvent acrylic

#### Liner

Green monosiliconized polyethylene

#### Tensile Strength MD

$12 \pm 2$  (N/cm)

TM 5004 by Afera

#### Elongation at Break MD

$265 \pm 25$  (%)

TM 5004 by Afera

#### Peel 180°

$14.48 \pm 1.7$  (N/cm)

TM 4001 by Afera

#### Adhesion to Steel

$5.5 \pm 1$  (N/25mm)

TM 5001 by Afera

#### Static Shear

Over 500 (h)

Afera (PSTC)

#### Rolling Ball Task

$16 \pm 5$ (cm)

PSTC-6 (PSTC)

#### Foam thickness

$860 \pm 70$  (mic)

#### Performing Temp

M-30 100°C

#### Shot passage Temp

T-40 +120°C

Effective: September 2016