



**ATLAS
TAPES**

Euromount DS DS 206.8

TECHNICAL DATA SHEET

DESCRIPTION:

Black closed cell polyethylene foam, solvent based acrylic adhesive suitable for mounting applications.

APPLICATIONS:

- Mounting applications.
- Fixing
- Automotive mounting.

ATHENS
68 Varis Avenue
16673 Voula, Greece
Tel.: +30 210 8995388

ATALANTI
3rd km Skala Atalanti Road
35200 Atalanti, Greece
Tel.: +30 22330 23725

www.atlas-tapes.gr
info@atlas-tapes.gr

ALL ABOUT TAPES



NOMINAL VALUES:

Backing

Black closed-cell polyethylene foam

Adhesive

Clear self cross linked solvent acrylic

Liner

Green monosiliconized polyethylene

Tensile Strength MD

12 ± 2 (N/cm)

TM 5004 by Afera

Elongation at Break MD

265 ± 25 (%)

TM 5004 by Afera

Peel 180°

14.48 ± 1.7 (N/cm)

TM 4001 by Afera

Adhesion to Steel

5.5 ± 1 (N/25mm)

TM 5001 by Afera

Static Shear

Over 500 (h)

Afera (PSTC)

Rolling Ball Task

16 ± 5 (cm)

PSTC-6 (PSTC)

Foam thickness

860 ± 70 (mic)

Performing Temp

M-30 100°C

Shot passage Temp

T-40 +120°C