



**ATLAS  
TAPES**

ATHENS  
68 Varis Avenue  
16673 Voula, Greece  
Tel.: +30 210 8995388

ATALANTI  
3rd km Skala Atalanti Road  
35200 Atalanti, Greece  
Tel.: +30 22330 23725

[www.atlas-tapes.gr](http://www.atlas-tapes.gr)  
[info@atlas-tapes.gr](mailto:info@atlas-tapes.gr)

---

## ADHESIVE TAPE

### Double Sided PP Tape

#### TECHNICAL DATA SHEET

ALL ABOUT TAPES



---

#### FILM PROPERTIES

##### Type of Film

Biaxially Oriented Polypropylene

##### Film Thickness ( $\mu\text{m}$ )

$28 \pm 2$

TM 5006 (Afera)

##### Tensile Strength MD

$100 \pm 20$  (N/25mm)

TM 5004 by Afera

##### Elongation at Break

$170 \pm 40$  (%)

TM 5004 by Afera

##### Liner

Two-sided Siliconized Paper

---

#### ADHESIVE PROPERTIES

##### Type of Adhesive

Hot Melt (Solvent-free)

##### Peel Adhesion on Stainless Steel

$17 \pm 4$  (N/25mm)

TM 5001 by Afera

##### Adhesive Color

White

Transparent

---

The recommended storage conditions for this product are around 21 °C and 50% relative humidity. Prior to use, carefully check that the contact surfaces are totally dry and clean from oil, grease and dust. The data stated above cannot be considered as binding by contract or by specifications. They correspond to the average values obtained from the tests carried out according to Atlas Tapes norms, in conformity with AFERA norms. Tests are carried out on samples taken from our standard production. These data may vary without any notice – the updated typical value sheets can be forwarded at any time. Since many different factors may influence the product's performance, we recommend testing the product by any application. We remain at your disposal for any further information or recommendations.