



**ATLAS
TAPES**

PP Acrylic 25my AC 518LN

TECHNICAL DATA SHEET

DESCRIPTION:

High-grade water based acrylic tape.
Carrier BOPP 25my film, with 20my adhesive for manual carton sealing packaging applications.
Low noise properties.

APPLICATIONS:

- Manual carton sealing.
- Adhesion on uneven surfaces due to high amount of adhesive.
- Particularly suitable for light-weight non-critical packaging applications.
- Suitable for cold and hot temperatures.

PROPERTIES:

- Environmentally friendly and ecological adhesive.
- Moisture compatible after application.
- UV resistant adhesive.
- Resistance to temperature changes.
- Longevity of application

ATHENS
68 Varis Avenue
16673 Voula, Greece
Tel.: +30 210 8995388

ATALANTI
3rd km Skala Atalanti Road
35200 Atalanti, Greece
Tel.: +30 22330 23725

www.atlas-tapes.gr
info@atlas-tapes.gr

ALL ABOUT TAPES



NOMINAL VALUES:

Backing

Biaxially Oriented Polypropylene (BOPP)

Adhesive

Acrylic (Water-based)

Tensile Strength MD

130 ± 30 (N/mm²)

TM 5004 by Afera

Elongation at Break MD

140 ± 30 (N/mm²)

TM 5004 by Afera

Adhesion to Steel

5.5 ± 1 (N/25mm)

TM 5001 by Afera

Shear to Steel

Over 170 (h, 25mm x 25mm on stainless steel, 23°C)

TM 5012 by Afera

Rolling Ball Task

Under 3 (cm)

PSTC-6 (PSTC)

Film thickness

25 ± 1 (mic)

Film Colors

Transparent

Adhesive Color

Transparent

Brown

White