

ATHENS 68 Varis Avenue 16673 Voula, Greece Tel.: +30 210 8995388 ATALANTI 3rd km Skala Atalanti Road 35200 Atalanti, Greece Tel.: +30 22330 23725 www.atlas-tapes.gr info@atlas-tapes.gr

ALL ABOUT TAPES

PP Acrylic 25my N-MACH AC 516N TECHNICAL DATA SHEET



DESCRIPTION:

High-grade water based noisy acrylic tape. Carrier BOPP 25my film, with 18my adhesive for manual carton sealing packaging applications.

APPLICATIONS:

- Manual carton sealing.
- Automatic carton sealing.
- · Adhesion on uneven surfaces due to high amount of adhesive.
- Particularly suitable for light-weight non-critical packaging applications.
- Suitable for cold and hot temperatures.

PROPERTIES:

- Environmentally friendly and ecological adhesive.
- Moisture compatible after application.
- UV resistant adhesive.
- Resistance to temperature changes.
- Longevity of application

NOMINAL VALUES:

Backing

Biaxially Oriented Polypropylene (BOPP)

Adhesive

Acrylic (Water-based)

Tensile Strength MD

 $130 \pm 30 (N/mm2)$

TM 5004 by Afera

Elongation at Break MD

140 ± 30 (N/mm2)

TM 5004 by Afera

Adhesion to Steel

 $5.2 \pm 1 (N/25mm)$

TM 5001 by Afera

Shear to Steel

Over I50 (h, 25mm x 25mm on stainless steel, 23°C)

TM 5012 by Afera

Rolling Ball Task

Under 3 (cm)

PSTC-6 (PSTC)

Film thickness

25 ± I(mic)

Film Colors Transparent 🛮

Adhesive Color Transparent ✓ Brown White ✓