

PP Hot Melt 25mic HM 70I

TECHNICAL DATA SHEET

ATHENS 68 Varis Avenue 16673 Voula, Greece Tel.: +30 210 8995388 ATALANTI 3rd km Skala Atalanti Road 35200 Atalanti, Greece Tel.: +30 22330 23725 www.atlas-tapes.gr info@atlas-tapes.gr

ALL ABOUT TAPES



DESCRIPTION:

Hot melt based synthetic rubber tape. Carrier BOPP 25mic film suitable for manual carton sealing packaging applications.

APPLICATIONS:

- High initial tack proves suitable for recycled cartons.
- Manual carton sealing
- Adhesion on uneven surfaces due to excellent adhesive initial power
- Suitable for all sorts of packaging applications and light carton sealing.

PROPERTIES:

- Increased initial tack
- Moisture compatible after application
- Instant adhesion
- Resistant to temperature changes
- · Longevity of application

NOMINAL VALUES:

Backing

Biaxially Oriented Polypropylene (BOPP)

Adhesive

Hot Melt (Solvent-free)

Tensile Strength MD

 $130 \pm 30 (N/mm2)$

TM 5004 by Afera

Elongation at Break MD

140 ± 30 (%)

TM 5004 by Afera

Adhesion to Steel

9 ± 2 (N/25mm)

TM 5001 by Afera

Shear to Steel

Over 200 (h, 25mm x 25mm on stainless steel, 23°C)

TM 5012 by Afera

Rolling Ball Task

Under I0 (cm)

PSTC-6 (PSTC)

Film thickness

25 ± I(mic)

Film Colors Transparent

✓

Adhesive Color Transparent ✓ Brown ■ White □